

## WIKO® Ultimate Elongation (white, black, grey)

Declaration of Performance (DoP) Nr.: 111230SWG03

- |   |   |
|---|---|
| 1. Product type:                                  | Ultimate Elongation (white, black, grey)  |
| 2. Identification number:                         | See product packaging for batch number  |
| 3. Intended use:                                  | Joint sealant for façade elements for interior and exterior use<br>F-EXT-INT 25HM<br>Sealant for non-load-bearing joints in interior and exterior floors<br>PW-EXT-INT 25HM |
| 4. Producer:                                      | WIKO KLEBETECHNIK Sp.zo.o.<br>ul. Ekonomiczna 8<br>42-271 Częstochowa   |
| 5. Authorised representative:                     | -   |
| 6. System for assessing constancy of performance: | System 3 for fire behaviour   |
| 7. Harmonised standard:                           | EN 15651-1: F-EXT-INT 25HM<br>EN 15651-4: PW-EXT-INT 25 HM  |
| 8. Notified organisation:                         | SKZ Tecona GmbH, Identification number 1213   |

9. Key feature	Performance	Harmonised techn. specification	
Fire behaviour	Class E	<b>EN 15651-1:2012</b> <b>EN 15651-4:2012</b>	
Release of chemicals hazardous to health and/or the environment	rated		
<b>Water and air tightness</b>			
Stability	≤ 3 mm		
Volume loss	≤ 10%		
Resilience	≥ 70%		
Tensile behaviour: Secant modulus at 23°C	≥ 0,4 MPa		
Tensile behaviour: Secant modulus at -20°C	≥ 0,6 MPa		
Tensile behaviour under prestressing	NF		
Adhesion/elongation behaviour at different temperatures	NF		
Adhesion/elongation behaviour under preload after immersion in water	NF		
Adhesion/elongation behaviour after exposure to	NF		
heat, salt water and artificial light	≤ 12 mm		
Durability	passed		
			NF = no failure

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

  
 WIKO Klebetechnik Sp. z o.o.  
 ul. Ekonomiczna 8 • 42-271 Częstochowa  
 Tel.: +48 34 37258-58  
 Fax: +48 34 3711114  
 info.pl@gluetec-group.com  
 www.gluetec-group.com  
 CEO  
 Greußenheim, 14.01.2025