

WIKO® Ultimate Elongation (white, black, grey)

Declaration of Performance (DoP) Nr.: 111230SWG04

- | | |
|---|---|
| 1. Product type: | Ultimate Elongation (white, black, grey) |
| 2. Identification number: | See product packaging for batch number |
| 3. Intended use: | Joint sealant for façade elements for interior and exterior use
F-EXT-INT 25HM
Sealant for non-load-bearing joints in interior and exterior floors
PW-EXT-INT 25HM |
| 4. Producer: | WIKO KLEBETECHNIK Sp. z o.o.
ul. Ekonomiczna 8
42-271 Częstochowa |
| 5. Authorised representative: | - |
| 6. System for assessing constancy of performance: | System 3 for fire behaviour |
| 7. Harmonised standard: | EN 15651-1: F-EXT-INT 25HM
EN 15651-4: PW-EXT-INT 25 HM |
| 8. Notified organisation: | SKZ Tecona GmbH, Identification number 1213 |

9. Key feature	Performance	Harmonised techn. specification
Fire behaviour	Class E	EN 15651-1:2012 EN 15651-4:2012
Release of chemicals hazardous to health and/or the environment	rated	
Water and air tightness		
Stability	≤ 3 mm	
Volume loss	≤ 10%	
Resilience	≥ 70%	
Tensile behaviour: Secant modulus at 23°C	≥ 0,4 MPa	
Tensile behaviour: Secant modulus at -20°C	≥ 0,6 MPa	
Tensile behaviour under prestressing	NF	
Adhesion/elongation behaviour at different temperatures	NF	
Adhesion/elongation behaviour under preload after immersion in water	NF	
Adhesion/elongation behaviour after exposure to	NF	
heat, salt water and artificial light	≤ 12 mm	
Durability	passed	
		NF = no failure

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



WIKO Klebetechnik Sp. z o.o.
 ul. Ekonomiczna 8 • 42-271 Częstochowa
 Tel.: +48 34 37258-58
 Fax: +48 34 3711114
 info.pl@gluetec-group.com
 www.gluetec-group.com

Fadi Ali Adib
 CEO

Greußenheim, 16.07.2026