

WIKO® MS Polymer (white, black, grey)

Declaration of performance (DoP) Nr. 0316351SWG04

1. Product type: MS Polymer (white, black, grey)
2. Identification number: See product packaging for batch number
3. Intended use: 1-component hybrid polymer sealant, neutral curing.
Sealant for façade elements: Type F-EXT-INT-CC 20HM
Sealant for joints in sanitary areas: XS3
Joint sealant for pedestrian walkways: EXT-INT-CC 20HM
4. Manufacturer: WIKO KLEBETECHNIK Sp. z o.o. ul. Ekonomiczna 8, 42-271 Częstochowa
5. Authorised representative: -
6. System of assessment of constancy of performance: 3 plus 3
7. Harmonised standard: EN 15651-1: 2017-02, EN 15651-3: 2017-02, EN 15651-4: 2017-02
8. Notified body: ITC (NB-Nr. 1023)

9. Key feature	Performance	Harmonised technical specification
Fire behaviour	Class E	EN 15651-1: 2017-02 Conditioning: Method B Substrates: Aluminium EN 15651-3: 2017-02 Conditioning: Method B Substrates: Aluminium EN 15651-4: 2017-02 Conditioning: Method B Substrates: Aluminium
Release of chemicals hazardous to health and / or the environment	Rated	
Water and air tightness		
a) Stability	≤ 3mm	
b) Volume loss	≤ 5%	
c) Resilience	≥ 60%	
d) Tensile properties at 23 °C	≥ 0,4 MPa	
e) Tensile properties in cold climates (-30 °C)	≥ 0,6 MPa	
f) Tensile properties under preload in cold climates (-30 °C)	NF	
g) Tensile properties under preload at different temperatures	NF	
h) Tensile properties under preload after immersion in water	NF	
Durability	NF	
Microbiological growth	3	
Tear resistance	NF	NF = no failure

10. The performance of the product referred to in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



WIKO Klebetechnik Sp. z o.o.
ul. Ekonomiczna 8 • 42-271 Częstochowa

Tel.: +48 34 37258-58

Fax: +48 34 3711114

info.pl@gluetec-group.com

www.gluetec-group.com

Fadi Ali Adib

CEO

Greußenheim, 16.07.2026